

CASE SEALER



CT 205 TBR CASE SEALER

Taping is the application of adhesive tape to, for example, a box or other surface. In the packaging industry, tape is often used to seal something, in most cases a box or package. In addition, tape is also used to bundle products, to mark products, to communicate a message or to prevent theft.

The ultimate goal of taping is to store and / or ship your products without damage, so that they arrive at your customer in perfect condition. Packaging tape or adhesive tape can be applied manually, with a table dispenser or by machine.

Machine with manual feed

The CT 205 TBR is an automatic case sealer suitable for PP or PVC tape from 25 mm to 50 mm.

The CT 205 TBR is particularly suitable for long, narrow boxes, as there are 4 horizontal conveyor belts, two at the top and two at the bottom, running parallel to the tape heads. After filling the box, the operator folds the top cover and inserts the box manually into the machine. The tape machine automatically adjusts to the width and height of the box, after which the top and bottom are automatically closed with tape. With the CT 205 TBR it is possible to professionally close hundreds of packages per day.



Options:

- 67 cm and 82 cm box width
- Wheels
- Extra transport / roller conveyors
- Direct printing / coding / labeling



Technical data:	
Machine dimensions (H x W x D)	1827 x 1635 x 1049 mm
Closure	Top and bottom
Consumable	PP / PVC tape
Tape - outer diameter	360 mm (max)
Tape - core diameter	76 mm
Tape - width	25 - 50 mm
Package - length	min 150 mm - max ∞
Package - width	130 mm - 520 mm
Package - height	100 mm - 500 mm
Capacity	600 packages / hour
Transport	Top and bottom - 22 meter / hour
Protection	IP 54
Power supply	380 V / 50 Hz / 3 phases
Weight	240 kg

Cyklop UK Limited Unit 2, Generation Business Park Barford Road St. Neots Cambridgeshire PE19 6YQ



