

CASE SEALER



CT 203 SD CASE SEALER

Taping is the application of adhesive tape to, for example, a box or other surface. In the packaging industry, tape is often used to seal something, in most cases a box or package. In addition, tape is also used to bundle products, to mark products, to communicate a message or to prevent theft.

The ultimate goal of taping is to store and / or ship your products without damage, so that they arrive at your customer in perfect condition. Packaging tape or adhesive tape can be applied manually, with a table dispenser or by machine.

Machine with side transport

The CT 203 SD is a semi-automatic case sealer suitable for PP or PVC tape from 25 mm to 50 mm. After filling the box, the operator folds the top cover and inserts the box manually into the machine. Then the top and bottom are automatically closed with tape. The machine can easily be manually adjusted to the required height and width, which is good when the package size to be processed changes little or not at all. The boxes are transported by means of motorised side conveyors, which ensure that the packages are perfectly aligned and a good seal is quaranteed.

With the CT 203 SD it is possible to professionally close hundreds of packages per day.



Options:

- 67 cm and 82 cm package width
- Wheels
- Extra transport / roller conveyors
- Filling station & box erector
- Direct printing / coding / labeling



Cyklop UK Limited Unit 2, Generation Business Park Barford Road St. Neots Cambridgeshire **PE19 6YQ**

Technical data:	
Machine dimensions (H x W x D)	1686 x 1162 x 895 mm
Closure	Top and bottom
Consumable	PP / PVC tape
Tape - outer diameter	360 mm (max)
Tape - core diameter	76 mm
Tape - width	25 - 50 mm
Packaging - length	min 150 mm - max ∞
Packaging - width	100 mm - 520 mm
Packaging - height	100 mm - 520 mm
Capacity	1.000 boxes / hour
Transport	Side transport - 22 meter / hour
Protection	IP 54
Power supply	380 V / 50 Hz / 3 phase
Weight	144 kg



