

CASE SEALER



CT 203 SDT CASE SEALER

Taping is the application of adhesive tape to, for example, a box or other surface. In the packaging industry, tape is often used to seal something, in most cases a box or package. In addition, tape is also used to bundle products, to mark products, to communicate a message or to prevent theft.


The ultimate goal of taping is to store and / or ship your products without damage, so that they arrive at your customer in perfect condition. Packaging tape or adhesive tape can be applied manually, with a table dispenser or by machine.

Machine with top and side transport

The CT 203 SDT is a semi-automatic case sealer suitable for PP or PVC tape from 25 mm to 75 mm.

The CT 203 SDT is particularly suitable for high, narrow boxes, because of the horizontal transport function and the top transport function.

After filling the box, the operator folds the top cover and inserts the box manually into the machine. Then the top and bottom are automatically closed with tape. The machine can easily be manually adjusted to the required height and width, which is good when the package size to be processed varies little. With the CT 203 SDT it is possible to professionally close hundreds of packages per day.



Options:

- 67 cm package width
- Wheels
- Extra transport / roller conveyors
- Direct printing / coding / labeling



Technical data:	
Machine dimensions (H x W x D)	1684 x 1166 x 892 mm
Closure	Top and bottom
Consumable	PP / PVC tape
Tape - outer diameter	360 mm (max)
Tape - core diameter	76 mm
Tape - width	25 - 75 mm
Package - length	min 150 mm - max ∞
Package - width	100 mm - 500 mm
Package - height	100 mm - 500 mm
Capacity	800 packages / hour
Transport	Top and side - 22 meter / hour
Protection	IP 54
Power supply	380 V / 50 Hz / 3 phases
Weight	130 kg

Cyklop UK Limited Unit 2, Generation Business Park Barford Road St. Neots Cambridgeshire PE19 6YQ



