



M-Pac V

STRAPPING MACHINE

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

M-Pac V

Strapping machine

The M-Pac V is the latest semi-automatic strapping machine from Cyklop. The M-Pac V is used for strapping various packages with PP strap. With the new M-Pac V you can choose between stroke tensioning (suitable for light packages / products that damage quickly) and torque tensioning (for stronger tension). The welding time and temperature are easily adjustable, which allows the machine to be used in a wide variety of applications. The frame is adjustable in height as standard and has robust swivel wheels. In addition, the M-Pac V is a silent strapping machine (57 dB) and therefore suitable for use in, for example, an office environment.

Easy maintenance

Access to the aggregate has been improved, so that possible (daily) maintenance is easier to carry out. The electrical parts of the machine are housed in a different compartment than the aggregate, the aggregate which helps when carrying out the (daily) maintenance. The M-Pac V has a direct drive with less moving parts which makes it easy to maintain and keeps operation cost low. The table top is hinged, but is easy to remove if necessary.

This compact, affordable, heavy-duty strapping machine offers reliability, ease of operation, simple maintenance and low running costs.



[< Click here for a video of the M-Pac V >](#)



Technical specifications:

Consumable	PP strap: 5, 6, 9, 12, 15,5 mm
Dimensions (WxHxD)	780 x (775-925) x 543 mm
Package size (WxH)	Min. 100 x 30 mm
Package weight	Max. 40 Kg
Strap coil	Core diameter 200 mm
	Outer diameter 420 mm
	Width 200 mm
Strap tension	Up to 450N
	Torque or Stroke tensioning
Sealing	Heat seal
Heating time	45 seconds
Weight	56 kg
Noise	max. 57,2 dB
Power supply	230 V, 1 phase, 50 Hz, 0,35 kW

Cyklop UK Limited
Unit 2, Generation Business Park
Barford Road
St. Neots
Cambridgeshire
PE19 6YQ

+44 1480 216777
www.cyklop.co.uk
info@cyklop.co.uk

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING