



AMPAG BOXER II-S

STRAPPING MACHINE

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

The Ampag Boxer II-S automatic strapping machine has a smaller strapping head and is therefore very suitable for strapping small products or products with an unusual shape, such as PVC pipes.

Advantages

- For PP strap: 5, 9, 12 mm
- Up to 55 straps per minute
- Automatic re-feed function in the event of an ejection fault
- Easy operation with foot pedal
- Automatic strap ejection system in the event of strapping without package
- Easy and simple strap insertion
- High reliability and stability, low maintenance
- Quick to heat (25 sec.)
- Counter
- Height adjustment



Options

- Tabletop switch / photocell



Technical data	
Speed	Up to 55 straps/minute
Minimum package size	40 mm x 30 mm (W x H) round Ø 50 mm
Arch size	650 x 450 mm
Strapping material	PP 5, 9 and 12 mm
Strap coil	Core diameter: 200 mm Outer diameter: 420 mm Width: 190 mm
Strap tension	50 – 450 N
Strapping	Heat seal
Noise	78 - 85 dB(A)
Warm up time	approx. 25 sec.
Power supply	230 V, 1 phase, 50 Hz, 0,74kVa
Machine weight	approx. 160 kg
Colour	RAL 5003

Cyklop UK Limited
 Unit 2, Generation Business Park
 Barford Road
 St. Neots
 Cambridgeshire
 PE19 6YQ

+44 1480 216777
www.cyklop.co.uk
info@cyklop.co.uk

