



CT 303 SD

CASE SEALER

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

In the packaging industry, tape is often used to seal boxes. Taping is therefore of great importance in the damage free storage and shipping of your products, so they arrive at your customer in perfect condition. Taping machines from Cyklop ensure a reliable and efficient taping process and are easy to set up and operate. The (semi-)automatic taping machines can be operated separately but are also perfectly integrable with other Cyklop machines in your packaging line.

The CT 303 SD is a semi-automatic case sealer suitable for PP and PVC tape and perfectly designed to be placed next to a packaging table. After filling the box the operator folds down the upper flaps manually and feeds the box into the case sealer where top and bottom flaps are automatically sealed with tape.

The machine is easily adjusted to the required box width and height. The side belt conveyors are driven by one motor to ensure a simultaneous transport speed and a perfect box sealing.

With the CT 303 SD, it is possible to close thousands of packages per day professionally.



Standard version of the CT 303 SD

Options:

- Infeed and outfeed conveyors
- Caster wheels
- 3-flap closing device



Closer view of CT 303 SD

Technical data:	CT 303 SD	CT 303 SD 65	CT 303 SD 80
Box length (mm)	150 - ∞	150 - ∞	150 - ∞
Box width (mm)	100 - 510	100 - 660	100 - 810
Height (mm)	100 - 510	120 - 660	120 - 810
Performance (Boxes/h)	Up to 1400		
Box sealing	Top and bottom		
Conveyor height	650 - 750 mm		
Conveyor speed	24 m/min		
Height transport belts (mm)	65	90	
Power supply	230V/50Hz/1Ph/0,22kW		
Tape	PP or PVC tape		
Tape width	50 mm (optional 75 mm)		
Machine dimensions LxWxH (mm)	990x965x1428	990x1146x1544	990x1297x1694
Machine weight (kg)	130	135	140

Cyklop UK Limited
 Unit 2, Generation Business Park
 Barford Road
 St. Neots
 Cambridgeshire
 PE19 6YQ

+44 1480 216777
www.cyklop.co.uk
info@cyklop.co.uk

