



LGT 260

BATTERY DRIVEN STRAPPING TOOL

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

LGT 260

BATTERY DRIVEN STRAPPING TOOL

The LGT 260 is a powerful and reliable battery driven strapping tool for strapping with PP or PET strap. This device combines all necessary operations - tensioning, welding, and cutting - in one. The LGT 260 is light weight and ergonomically balanced. The operation is very simple, allowing an operator to make a strap up to six times faster compared to a buckle or seal device. The LGT 260 can be used in a manual, semi-automatic or fully automatic mode and comes with a powerful Bosch Li-Ion 18V 4.0 Ah battery, allowing you to make up to 500 strappings per charge.

The tension force can be set variably, up to 2800 N, making this device a real all-rounder. Extremely suitable for strapping, paper, logistics, metal, wood or construction industry.

Strapping in multiple places

Do you want to strap at different places within your company? The LGT 260 works with a battery and is therefore mobile and ideal for strapping at various locations.

Our QPWK-S is a handy strap dispenser, meaning you will always have your strapping tool and strap at hand. Thanks to its sturdy construction and robust wheels, you can take the QPWK-S with you wherever you go.

Options:

- Strap dispenser QPWK-S
- StrapBandit - for pallet strapping
- Extra Bosch battery



[< Click here for a video of the LGT 260 >](#)



Technical specifications:

Consumable	PET 13-19 mm wide, 0,5-1,2 mm thick PP 13-19 mm wide, 0,5-1,2 mm thick
Dimensions (LxWxH)	355 x 145 x 145 mm
Weight	3,4 kg
Operation	Manual & (semi-)automatic
Tension force	400 - 2800 N
Battery	Bosch Li-Ion 18 V / 4,0 Ah
Charging time	65 min.
Straps per charge	Max 500
Battery charger voltage	230 V
Working temperature	-10° C to + 40° C

Cyklop UK Limited
Unit 2, Generation Business Park
Barford Road
St. Neots, Cambridgeshire
PE19 6YQ

+44 1480 216777
www.cyklop.co.uk
info@cyklop.co.uk

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING