



# LAPOMATIC

PAPER TAPE DISPENSER

**CYKLOP**<sup>®</sup>  
GLOBAL PACKAGING SOLUTIONS

STRAPPING  
WRAPPING  
CODING  
TAPING

Paper tape is the environmentally friendly solution for closing boxes. After use, the packaging box can be recycled, including the adhesive tape. Due to the direct and strong adhesion, paper tape is also suitable for heavy packaging. Another major advantage of paper tape is that it cannot be removed without damaging the box, which has a preventive effect against theft.

Paper tape can be divided into two types: self-adhesive paper tape and gummed paper tape. Gummed paper tape only sticks after the adhesive layer is activated with water. A dispenser is therefore required for application.

**Dispenser**

The paper tape dispenser Lapomatic is an electric dispenser for gummed paper tape, with a water resistant, soft touch control panel. Suitable for closing large numbers of boxes with gummed paper tape.

The Lapomatic has an electronic control system for the cutting of paper tape. This means that the dispenser cuts the pre-set length every time, even when the repeat function is switched on. The Lapomatic is reliable, low-noise, user-friendly and robust. All corrosion sensitive parts are polished or galvanized, which means a long lifetime and low maintenance.



**Options:**

- Outer roll diameter up to 300 mm
- Start with foot pedal
- With battery [Lapomatic Battery](#)
- 200 mm width tape [Lapomatic 200](#)
- Dimensions detection [Lapomagic](#)
- Printer option [LCM 100](#)

[< Click here for a video of the Lapomatic >](#)



| Technical specifications: |  |
|---------------------------|--|
| Speed                     | 55 mtr / min   |
| Dimensions (HxWxD)        | 250 x 290 x 450 mm   |
| Consumable                | Any type of gummed paper tape*<br>*also for re-inforced tape     |
| Roll width                | 20 - 100 mm  |
| Selected length           | 100 - 1.150 mm   |
| Outer roll diameter       | 200 mm*<br>*300 mm width is optional                             |
| Water reservoir           | 1300 cc  |
| Temperature water         | Adjustable (50° - 75° - 100°)                                    |
| Power                     | 230 V / 50 Hz / 1 fase<br>Power cut-off after 30 min without use |
| Weight                    | 12 kg  |
| Noise                     | < 70 dB  |

Cyklop UK Limited  
 Unit 2, Generation Business Park  
 Barford Road  
 St. Neots  
 Cambridgeshire  
 PE19 6YQ  
 +44 1480 216777  
[www.cyklop.co.uk](http://www.cyklop.co.uk)  
[info@cyklop.co.uk](mailto:info@cyklop.co.uk)

